



# TILLMAN®

## 954



# CUT RESISTANCE GLOVES

Moderate Cut Hazard & High Abrasion Risk with a Sandy Nitrile Coating



## FEATURES

- Proprietary HPPE blend provides excellent cut, ANSI A4, and abrasion, EN388 4, resistance for longer wear time and longer glove life.
- Sandy nitrile coating provides a superior grip and won't slip when trying to get a hold on wet or dry surfaces.
- Increase worker confidence when handling rough or sharp components or objects.
- Seamless construction offers excellent dexterity and sense of touch.
- HPPE weave stretches and hugs the hand for a perfect fit.
- High vis color for easy hand visibility and compliance detection
- Breathable shell allows for heat to escape for all day comfort.
- Sizes Available: S, M, L, XL, 2X.

## APPLICATIONS

General duty, Material handling, Manufacturing, Sheet metal handling, Assembly line production, Parts handling, Automotive assembly, Carpentry, Construction, Glass handling, HVAC, Roofing



## PERFORMANCE DATA:



EN 388: 4543

- Abrasion Resistance - 4
- Cut Resistance - 5
- Tear Resistance - 4
- Puncture Resistance - 3




ANSI 105 (2016)

- Cut Resistance - A4

## PACKAGING INFORMATION

- Each pair is individually packaged on a header card
- ° Minimum Order Quantity: 6 pairs per size
- ° Case Quantity: 72 pairs per size

- 1 Super soft glass fiber blend liner.
- 2 Comfortable & breathable shell for all day wear.
- 3 Sandy nitrile coating provides a great grip and resists tears.
- 4 Able to withstand multiple launderings for longer life.
- 5 Great dexterity and tactical feel.
- 6 Colored cuff for easy size indication.



# TILLMAN®