



# SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

## Section 1: Product and Company Identification

Product Name: **KCI Solvent Based Anti-Spatter (Aerosol)**  
Product Identifier: Anti-Spatter  
Product Use: Prevents Spatter Build Up in Welding Operations  
Item Code(s): RW1620  
SDS Code: 001  
Manufacturer: KCI, Inc.  
Physical Address: 1721 Toal Street  
Charlotte, N.C. 28206  
Mailing Address: P.O. Box 26614  
Charlotte, N.C. 28221  
Business Phone: 704-372-8435  
Business Fax: 704-333-5955  
E-mail Address: info@kciincorporated.com  
Web Address: www.kciincorporated.com  
Emergency Phone: CHEMTREC (24-Hour) 1-800-424-9300  
Date of Preparation: August 24, 2007 (Revised September 26, 2018)  
OSHA Regulatory Status: Regulated  
WHMIS Classification: D1B, D2A, D2B, A

## Section 2: Hazards Identification

### CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

#### CLP/GHS Classification (1272/2008):

| Physical | Health                                                                                                                                                           | Environmental |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| None     | Eye Irritation Category 2A<br>Skin Irritation Category 2<br>Specific Target Organ Toxicity - Single<br>Exposure Category 3 (H335, H336)<br>Carcinogen Category 2 | None          |

EU CLASSIFICATION (67/548/EEC): Xn R40 (Carcinogen Category 2)

### Label Elements

WARNING! Contains methylene chloride



### Hazard Phrases

|      |                                    |
|------|------------------------------------|
| H315 | Causes skin irritation.            |
| H319 | Causes serious eye irritation.     |
| H335 | May cause respiratory irritation.  |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer.       |

**Precautionary Phrases**

|                          |                                                                                                                                  |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| P201                     | Obtain special instructions before use.                                                                                          |
| P261                     | Avoid breathing dust/fume/gas/mist/vapors/spray.                                                                                 |
| P264                     | Wash thoroughly after handling.                                                                                                  |
| P271                     | Use only outdoors or in a well-ventilated area.                                                                                  |
| P280                     | Wear protective gloves/protective clothing/eye protection/face protection.                                                       |
| P305 +<br>P351 +<br>P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337 +<br>P313           | IF EYE IRRITATION PERSISTS: Get medical advice/attention.                                                                        |
| P302 +<br>P352           | IF ON SKIN: Wash with plenty of soap and water.                                                                                  |
| P332 +<br>P313           | IF SKIN IRRITATION OCCURS: Get medical advice/attention.                                                                         |
| P362                     | Take off contaminated clothing and wash before reuse.                                                                            |
| P304 +<br>P340           | IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.                                        |
| P312                     | Call a POISON CENTER or doctor/physician if you feel unwell.                                                                     |
| P308 +<br>P313           | IF EXPOSED OR CONCERNED: Get medical advice/attention.                                                                           |
| P403 +<br>P233           | Store in a well-ventilated place. Keep container tightly closed.                                                                 |
| P405                     | Store locked up.                                                                                                                 |
| P501                     | Dispose of contents/container in accordance with local or national regulations.                                                  |

OTHER IMPORTANT HAZARDS: N/A

SUGGESTED HMIS RATING: Health | 2 | Flammability | 1 | Reactivity | 1 | Personal Protection | C |

SUGGESTED NATIONAL FIRE PROTECTION ASSOCIATION: Health | 2 | Flammability | 1 | Reactivity | 1 |

**Section 3: Composition and Information on Ingredients****SUBSTANCES:**

| Chemical Name                           | CAS#     | EINECS#   | EU Classification<br>(67/548/EEC) | GHS Classification<br>Regulation (EC) No<br>1272/2008                                                                                                                                                 | %   |
|-----------------------------------------|----------|-----------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Methylene Chloride<br>(Dichloromethane) | 75-09-2  | 200-838-9 | Xn (Carc Cat 2) R40               | Eye Irritation Category<br>2A (H319),<br>Skin Irritation Category<br>2 (H315),<br>Specific Target Organ<br>Toxicity Single<br>Exposure Category 3<br>(H335, H336),<br>Carcinogen Category 2<br>(H351) | >90 |
| Carbon Dioxide                          | 124-38-9 |           |                                   |                                                                                                                                                                                                       |     |

See Section 16 for further information on EU and GHS Classification.

---

## Section 4: First Aid Measures

---

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.

**INGESTION:** Unlikely due to being in aerosol form. Should actual ingestion occur, do not induce vomiting! Drink a glass of water or milk to dilute. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**EYE CONTACT:** Immediately flush with plenty of clear water for at least 15 minutes. Make sure to flush under the eyelids. Consult a physician for definitive treatment.

**SKIN CONTACT:** Remove with soap and water. Continue flushing with water for several minutes. Use skin cream to counter resulting dryness. Consult a physician if irritation continues or if large skin area is affected.

---

## Section 5: Fire Fighting Measures

---

**MEANS OF EXTINCTION:** For warehouse and storage conditions, use NFPA Class B extinguishers (CO<sub>2</sub>, dry chemical or universal aqueous film forming foam).

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure demand. Use water spray to cool fire exposed aerosol containers for containers can rupture violently from heat developed pressure.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Contents under pressure. In addition, when liquid or vapor comes into contact with flames or red hot metal, products of combustion will be created. Firemen should wear self-contained breathing apparatus.

**FLASH POINT / DETERMINATION:** None to boiling

**UPPER FLAMMABLE LIMIT:** N/Av

**LOWER FLAMMABLE LIMIT:** N/Av

**AUTO-IGNITION TEMPERATURE:** N/Av

**HAZARDOUS COMBUSTION PRODUCTS:** N/Av

**EXPLOSION DATA - SENSITIVITY TO MECHANICAL IMPACT:** N/Av

**EXPLOSION DATA - SENSITIVITY TO STATIC DISCHARGE:** N/Av

---

## Section 6: Accidental Release Measures

---

**LEAK / SPILL RESPONSE:** Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content should be contained as any other solvent spill. Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove all sources of ignition and use non-sparking equipment. Soak up material with inert absorbent. Flush area with water. All rinsate should be placed in safety containers and labeled for proper disposal.

**SPECIAL INSTRUCTIONS:** Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal considerations.

---

## Section 7: Handling and Storage

---

**HANDLING PROCEDURES / EQUIPMENT:** Avoid prolonged or repeated skin contact. Avoid breathing vapors.

**STORAGE REQUIREMENTS:** Store in area below 120°F (49°C). Do not incinerate (burn) containers. Assure can is in a secure place to prevent knocking over and accidental rupture. Always replace overcap when not in use. For store of pallet quantities, compliance with ANSI/NFPA 30B is recommended.

---

## Section 8: Exposure Controls / Personal Protection

---

**EYE PROTECTION:** Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact could occur, chemical splash proof goggles are recommended.

**SKIN PROTECTION:** For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing such as Sol-Vex® gloves or other clothing impervious to the ingredient listed in Section 2.

**ENGINEERING CONTROLS:** General ventilation (typically 10 air changes for hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system, may be needed to control air contamination below that of the lowest TLV/PEL rated ingredient from Section 2.

**EXPOSURE GUIDELINE LEVELS:** Since this product is a mixture, an OSHA or ACGIH exposure value is not available. In determination of any exposure procedures, protection or testing use the lowest rated ingredient in Section 2.

### Control Parameters

| Chemical Name                        | Exposure Limits                                                                                                                      |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Methylene Chloride (Dichloromethane) | 25ppm TWA OSHA PEL, 125 ppm STEL<br>50 ppm TWA ACGIH TLV<br>100 ppm TWA UK OEL, 300 ppm STEL<br>75 ppm TWA Germany AGS, 300 ppm STEL |
| Soya Lecithin                        | None Established                                                                                                                     |
| Carbon Dioxide                       | 5000 ppm TWA OSHA PEL<br>5000 ppm TWA ACGIH TLV, 30,000 ppm STEL                                                                     |

In the United States, 29 CFR 1910.1052 is the OSHA regulation on Occupational Exposure to Methylene Chloride. Assure compliance with these regulations.

---

## Section 9: Physical and Chemical Properties

---

|                                        |                                                   |
|----------------------------------------|---------------------------------------------------|
| PHYSICAL STATE:                        | Liquid / Gas                                      |
| ODOR and APPEARANCE:                   | Clear to white liquid with a chloroform-like odor |
| ODOR THRESHOLD:                        | N/Av                                              |
| SPECIFIC GRAVITY (H <sub>2</sub> O=1): | 1.32                                              |
| VAPOR PRESSURE (mm HG):                | 390                                               |
| VAPOR DENSITY (AIR=1):                 | 2.9                                               |
| EVAPORATION RATE (BA=1):               | 14.50                                             |
| BOILING POINT (°F):                    | 104°F                                             |
| FREEZE POINT (°F):                     | N/Av                                              |
| pH:                                    | N/Av                                              |
| COEFFICIENT OF WATER/OIL DISTRIBUTION: | N/Av                                              |
| DENSITY:                               | N/Av                                              |
| SOLUBILITY IN WATER (% by weight):     | 1.3                                               |
| % VOLATILE BY VOLUME:                  | 20.0% Wt. Max                                     |
| VOC'S:                                 | N/Av                                              |

---

## Section 10: Stability and Reactivity

---

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Heat, sparks, open flame, red hot metal, electrical arcs, high pressure in aluminum systems.

**MATERIALS TO AVOID (INCOMPATIBILITIES):** Strong oxidizing materials (i.e. oxygen, nitrogen, peroxide, oxidizers) and reactive metals (i.e. aluminum, potassium, sodium, etc).

**CONDITIONS OF REACTIVITY:** N/Av

**HAZARDOUS DECOMPOSITION BY-PRODUCTS:** CO, CO<sub>2</sub>, phosgene and /or HCl

**HAZARDOUS POLYMERIZATION:** Will not occur.

---

## Section 11: Toxicological Information

---

LD50 (oral, rat) = 1600 mg/Kg

LC50 (inhalation, rat) = 88,000 mg/m<sup>3</sup>/30 min

ROUTES OF ENTRY: Inhalation [Y] Eye Contact [Y] Skin Contact [Y] Skin Absorption [Y] Ingestion [N]

EXPOSURE LIMITS: Since this product is a mixture, an OSHA or ACGIH exposure value is not available. In determination of any exposure procedures, protection or testing use the lowest rated ingredient in Section 2.

IRRITANCY OF PRODUCT: N/Av

SENSITIZATION TO PRODUCT / MEDICAL CONDITIONS AGGRAVATED: Prolonged contact with high concentrations can lead to serious kidney and liver damage.

CARCINOGENICITY:

This product contains Methylene Chloride which has been shown to cause cancer in certain laboratory animals when exposed to high vapor concentration over an extended period of time. While not proven to be carcinogenic to humans, if it should be found to be so, risk to health would depend on level and duration of exposure. Exposure to vapor should be minimized until risk to humans has been determined.

TERATOGENICITY / MUTAGENICITY / REPRODUCTIVE TOXICITY: Negative or equivocal results have been obtained in mutagenicity test using mammalian cells or animals. Results of AMES bacterial tests have generally been positive suggesting that genotoxic potential does not appear to be a significant factor in the toxicity of methylene chloride.

TOXICOLOGICAL DATA: N/Av

---

## Section 12: Ecological Information

---

ENVIRONMENTAL EFFECTS: This product has not been tested for environmental effects.

IMPORTANT ENVIRONMENTAL CHARACTERISTICS: N/Av

AQUATIC TOXICITY: N/Av

---

## Section 13: Disposal Considerations

---

An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations. Collected rinsate materials from spills may be hazardous wastes, and therefore subject to local, state and federal regulations.

---

## Section 14: Transportation Information

---

THIS MATERIAL IS **HAZARDOUS** (Per 49 CFR 172.101) BY THE U.S. DEPARTMENT OF TRANSPORTATION.

### NON-BULK SHIPMENTS:

|                                                              |                        |
|--------------------------------------------------------------|------------------------|
| PROPER SHIPPING NAME:                                        | Aerosols               |
| HAZARD CLASS NUMBER and DESCRIPTION:                         | 2.2 (Nonflammable Gas) |
| UN IDENTIFICATION NUMBER:                                    | UN 1950                |
| PACKING GROUP:                                               | Not Applicable         |
| DOT LABEL(S) REQUIRED:                                       | Nonflammable Gas       |
| NORTH AMERICAN EMERGENCY RESPONSE<br>GUIDEBOOK NUMBER, 1996: | 126                    |

### SHIPMENTS:

MARINE POLLUTANT: This product does not contain any component designated by the DOT to be a Marine Pollutant (49 CFR 172.101, Appendix B).

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This material is considered as **DANGEROUS GOODS**. Use the above information for the preparation of Canadian shipments.

---

## Section 15: Regulatory Information

---

### US FEDERAL REGULATIONS

**OSHA CLASSIFICATION:** This product is classified as a "Hazardous Chemical" by definition of Hazard Communication Standard (29 CFR 1910.1200) Occupational exposures to methylene chloride are specifically regulated under 29 CFR 1910.1052

**CARCINOGEN STATUS:** Methylene chloride is listed by NTP as 'reasonably anticipated to be a human carcinogen' and by IARC as a Group 2B carcinogen.

**TOXIC SUBSTANCES CONTROL ACT (TSCA):** The product on this SDS, or all of its components, is listed under TSCA.

**SARA TITLE III, SECTION 313:** The following ingredients are subject to the reporting requirements of Section 313 of Title III of the Superfund and Reauthorization Act of 1986 and 40 CFR Part 372: Methylene Chloride (90.5%).

**CLEAN AIR ACT (CAA):** The following ingredients appear on the List of Hazardous Air Pollutants (HAP - 42 USC 7412, Title I, Part A, p112): None

**CLEAN WATER ACT (CWA):** The following ingredients appear on the CWA List of Hazardous Substances (40 CFR 116.4): None

**CALIFORNIA PROPOSITION 65:** The following ingredients appear of the Proposition 65 list(s): Methylene Chloride (C)

**NEW JERSEY RIGHT TO KNOW INFORMATION:** (5 most predominant ingredients / hazardous & non-hazardous)

Methylene Chloride CAS# 75-09-2

Carbon Dioxide CAS# 124-38-9

Soy Lecithin CAS# 8002-43-5)

**CANADIAN WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS):** This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

**DOMESTIC SUBSTANCES LIST (DSL):** The product on this SDS, or all of its components, is included in the DSL.

---

## Section 16: Other Information

---

### GHS Phrases for Reference (See Sections 2 and 3):

|      |                                    |
|------|------------------------------------|
| H315 | Causes skin irritation.            |
| H319 | Causes serious eye irritation.     |
| H335 | May cause respiratory irritation.  |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer.       |

### EU Classes and Risk Phrases for References (See Sections 2 and 3):

|            |                          |
|------------|--------------------------|
| Xi         | Irritant                 |
| Xn         | Harmful                  |
| Carc Cat 2 | Carcinogen Category 2    |
| R36        | Irritating to eyes.      |
| R40        | Possible risk of cancer. |

### Other:

|         |                                                           |
|---------|-----------------------------------------------------------|
| N/E     | Not Established                                           |
| N/Av    | Not Available                                             |
| N/Ap    | Not Applicable                                            |
| IARC    | International Agency for Research on Cancer               |
| ACGIH   | American Conference of Governmental Industrial Hygienists |
| NIOSH   | National Institute for Occupational Health and Safety     |
| TLV-TWA | Threshold Limit, Time Weighted Average                    |
| NAERG   | North American Emergency Response Guidebook               |
| WHMIS   | Workplace Hazardous Materials Information System          |

---

This SDS format meets ANSI Z400.1-1998, OSHA 1910.1200 and WHMIS requirements. KCI provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of KCI. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made.